


390

LOOSE COUNTERSINK

- HS
- two cutting edges
- countersink angle 180°
- RH rotation
- bore and crampling screw



to be used in conjunction with twist drills and dowel drills • for shallow countersinks in soft- and hardwood

<i>d</i>	<i>D</i>	<i>GL</i>	<i>Z</i>	<i>HS</i>	<i>TC</i>	<i>RH</i>	<i>LH</i>	<i>Part number</i>
4	10	25	2	•		•		390.040.100.HS.R
5	12	25	2	•		•		390.050.120.HS.R
5	15	25	2	•		•		390.050.150.HS.R
6	15	25	2	•		•		390.060.150.HS.R
6	16	25	2	•		•		390.060.160.HS.R
6	20	30	2	•		•		390.060.200.HS.R
8	16	25	2	•		•		390.080.160.HS.R
8	20	30	2	•		•		390.080.200.HS.R
8	22	30	2	•		•		390.080.220.HS.R
8	25	30	2	•		•		390.080.250.HS.R
10	20	30	2	•		•		390.100.200.HS.R
10	25	30	2	•		•		390.100.250.HS.R
10	30	30	2	•		•		390.100.300.HS.R
12	25	30	2	•		•		390.120.250.HS.R
12	30	30	2	•		•		390.120.300.HS.R